

Lumina

Shines in both loss prevention and advertising

KEY FEATURES

- > Highly reliable system with high detection rate
- > Quick and easy ad graphic placement
- > Can be synchronized with multiple systems
- > Sensitivity adjustment reduces false alarms
- > Built-in jammer detection
- > Network connection and I/O port for easy integration with other LP systems
- > People counting and alarm verification
- > RFID ready version available
- > Optional remote tuning capability can reduce maintenance costs and downtime
- > Optional booster-bag detection

SPECIFICATIONS

- > Frequency: 58 kHz, 8.2 MHz or RFID
- > Dimensions: 17.9" W x 66.1" H x 2.17" D (45.4 cm x 168 cm x 5.5 cm)
- > Base depth: 3.7" (9.5 cm)
- > Weight: 27.5 lbs (12.5 kg)
- > Advertising panel dimensions: 56.3" x 14.72" (56.3" x 14.1" visible)
- > Detection range: Up to 7' (between two pedestals)
- > Power requirement: 115V/60Hz or 230V/50Hz, 35W max, internal PS embedded (external power supply available)
- > Alarm mode: Buzzer and RGB alarm indicator
- > Operating temperature: 32° F - 95° F
- > Relative humidity range: 0 - 90%, non-condensing



FREQUENCY	BACKLIT?	ORDER CODE
58 kHz (AM)	Yes	PA450 AM TRX LGP
58 kHz (AM)	No	PA450 AM TRX
58 kHz (AM) + RFID	No	PA450 AM TRX RFID
8.2 MHz (RF)	Yes	PA450 RF TRX LGP
8.2 MHz (RF)	No	PA450 RF TRX
8.2 MHz (RF) + RFID	No	PA450 RF TRX RFID
RFID only	No	PA450 UHF RFID