

Intrepid 6M

Sturdy aluminum rf system for 6 foot door openings

Lightweight yet tough thanks to its aluminum construction, the Intrepid 6M offers exceptional detection rate while easily fitting into any store environment.

The Intrepid 6M's Active Response System automatically adjusts the system to block interference ensuring reliable operation even in challenging environments.

KEY FEATURES

- ▲ Highly reliable system with high detection rate
- ▲ Lightweight metal construction
- ▲ Active Response System monitors store environment and automatically adjusts the system to reduce interference
- ▲ Can be synchronized with multiple systems



Intrepid 6M

Sturdy aluminum RF system for 6 foot door openings

SPECIFICATIONS	
Height	59.84"
Width	15.75"
Depth	1.97"
Weight	16 lbs.
Detection range	Up to 6 feet per pedestal (3 feet per side)
Power requirement	17 VAC / 1A (an external power supply required)
Alarm mode	Buzzer and RGB alarm indicator
Operating frequency	8.2 MHz \pm 200 Hz
Operating temperature	32° F - 95° F
Relative humidity range	0 - 90%, non-condensing
Materials composition	Plastic, acrylic, steel

ORDER CODES

ANT-MPP400S RX CDUS (Receiver antenna)

ANT-MPP400S TX CDUS (Transceiver antenna)

NOTE:

One receiver and one transceiver antenna are required for a complete system for one door.



PROSEGUR
SECURITY

(800) 405-1832 // PROSEGUR.US